

# UNO-2484G (Luxuriant I/O Solution)

Intel® Core™ i7/i5/i3 Regular-Size  
Box PC with 8 x COM, 8 x USB, 4 x GbE,  
1 x mPCIe, HDMI, DP

NEW



## Features

- Intel® Core™ i7/i5/i3 Processor with 8GB DDR4 built-in memory
- 4 x GbE, 4 x USB 3.0, 4 x USB2.0, 1 x HDMI, 1 x DP, 8 x RS232/422/485
- Compact fanless design
- Lockable I/O design
- Dedicated TPM2.0 micro controller designed for hardware security

## Introduction

Advantech's new generation UNO-2000 series of embedded automation computers are highly ruggedized, fanless, and modular designs. New UNO-2000 series implement universal, customized, and domain-specific ideas into modular design, which provides flexible, fast time-to-market support for a variety of applications. The series also includes iDOOR technology which supports automation feature-extensions such as multiple I/O peripherals, Industrial Fieldbus, and smart I/O communication. New UNO-2000 series include pocket, small, and regular-sized form-factors for different kinds of smart factory applications such as Equipment Connectivity (EC), Process Visualization (PV), Environment Management (EM), and Dispatch Management (DM).

## Specifications

### General

- **Certification** CE, FCC, UL, CCC
- **Dimensions (W x D x H)** 200 x 140 x 70 (7.8" x 5.6" x 2.8")
- **Form Factor** Regular Size
- **Enclosure** Aluminum Housing
- **Mounting** Stand, Wall, VESA (Optional), DIN-rail (Optional)
- **Weight (Net)** 1.6kg (3.53lbs)
- **Power Requirement** 10 - 36 V<sub>DC</sub>
- **Power Consumption** 55W (Typical), 95.2W (Max)
- **OS Support** Microsoft® Windows 7, 10, Advantech Linux

### System Hardware

- **BIOS** AMI EFI64 Mbit
- **Watchdog Timer** Programmable 255 levels timer interval, from 1 to 255 sec
- **Hardware Security** TPM2.0
- **Processor** 6th Gen Intel Core i7-6600U, 2.6GHz  
i5-6300U, 2.4GHz  
i3-6100U, 2.3GHz
- **Memory** Built-in 8GB DDR4 2133 MHz
- **Graphics Engine** Intel® HD Graphics 620
- **Ethernet** LAN A: Intel i219-IT GbE, 802.1Qav, IEEE1588/802.1AS, 802  
LAN B-D: Intel i210-IT GbE, 802.1Qav, IEEE1588/802.1AS, 802
- **LED Indicators** LEDs for Power, HDD, LAN (Active, Status), RTC  
Battery low
- **Storage** One mSATA (slot shared with mPCIe slot)  
Two drive bay for SATA 2.5" SSD/HDD (Support RAID 0/1)
- **Expansion** 1 x full-size mPCIe slot

### I/O Interfaces


- **Serial Ports** 8 x RS 232/422/485
- **LAN Ports** 4 x RJ45, 10/100/1000 Mbps IEEE 802.3u  
1000BASE-T Fast Ethernet
- **USB Ports** 4 x USB3.0, 4 x USB2.0
- **Displays** 1 x HDMI supports 1920 x 1080 @60Hz,  
1 x DP supports 3840 x 2160 @30Hz
- **Audio** Line-out
- **Power Connector** 1 x 2 Pins, Terminal Block

### Environment


- **Operating Temperature** -20 ~ 60°C (-4 ~ 140°F) @ 5 ~ 85% RH with 0.7 m/s airflow
- **Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)
- **Relative Humidity** 10 ~ 95% RH @ 40°C, non-condensing
- **Shock Protection** Operating, IEC 60068-2-27, 50G, half sine, 11 ms
- **Vibration Protection** Operating, IEC 60068-2-64, 3 Grms, random, 5 ~ 500 Hz, 1hr/axis (mSATA)
- **Ingress Protection** IP40

## Installation Scenario

### DIN-rail Mount Illustration




### VESA Mount Illustration




## Dimensions


Unit: mm



## Front I/O View



## Rear I/O View



## Ordering Information

| Part Number       | CPU generation | CPU      | RAM | mPCIe slot | iDoor | USB | COM | LAN | DP | HDMI |
|-------------------|----------------|----------|-----|------------|-------|-----|-----|-----|----|------|
| UNO-2484G-6732UAE | 6 Generation   | i7-6600U | 8G  | 1          | x     | 8   | 8   | 4   | 1  | 1    |
| UNO-2484G-6532UAE |                | i5-6300U |     |            |       |     |     |     |    |      |
| UNO-2484G-6332UAE |                | i3-6100U |     |            |       |     |     |     |    |      |

## Optional Accessories

- **96PSA-A150W24T2** Power Adapter 150W
- **96PSA-A120W24T2** Power Adapter 120W
- **1702002600** Power Cable US Plug 1.8 M (Industrial Grade)
- **1702002605** Power Cable EU Plug 1.8 M (Industrial Grade)
- **1702031801** Power Cable UK Plug 1.8 M (Industrial Grade)
- **1700000596** Power Cable China/Australia Plug 1.8 M (Industrial Grade)
- **UNO-2000G-VMKAE** UNO-2000 VESA Mount Kit
- **UNO-2000G-DMKAE** UNO-2484G DIN RAIL Kit
- **UNO-2000-LKAE** Cable lockable kit 10 units/per pack

## Operating System

- **20703WE7PS0009** WS7P X64 MUI V4.18 B023 Image
- **2070015318** WIN10 LTSB V6.01B056 for i7 version
- **2070015319** WIN10 LTSB V6.01B056 for i5/i3 version

Please note: If some optional modules are offered with the system, additional system certificates may be required in certain regions/countries. Please contact Advantech for certificate compliance.